

**Head Office**

17 - 19 David Lee Rd Hallam Victoria 3803  
PO Box 1143 Narre Warren MDC 3805  
T 03 9796 3333

atkar.com.au

**WA/SA Region**

PO Box 710 Joondaliup DC 6919  
T 08 6323 5662



# Vogl Maintenance Guide

To ensure the quality of your VoglFuge ceiling please observe the following instructions for care, maintenance and repair of your acoustic design ceiling.

**General Cleaning**

- > Slight surface soiling, dust deposits, etc can be brushed off the ceiling with a clean fine-hair broom.
- > Do not use water to clean the ceiling as this might impair the final coating.

**Maintenance and repair (new paint coat)**

Preparation for new paint coat:

- > Mend any minor damage caused by use (small notches, boreholes, etc.) by using painter's filler and then sanding and priming the spots.
- > Check the surfaces. Brush off any soiling with a clean, fine-hair broom. If necessary, use a damp cloth or fine sandpaper.

Application of new paint coat:

- > Observe the paint manufacturer's processing instructions and adhere to drying times.
- > All coatings on acoustic design ceilings must be applied with a roller.
- > Note: A new paint coat on the acoustic design ceiling will have no impact on the acoustic effect.

**For any advice or support on your VoglFuge Ceiling Panels please contact Atkar Group on 03 9796 3333.**

